



NEW TIRE SHINE SDS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Name on Label: PROFESSIONALS CHOICE NEW TIRE SHINE

Other Identification: NONE

Use of the substance/mixture: TIRE DRESSING

Company name : MOORE OIL COMPANY
4033 WEST CUSTER AVE
MILWAUKEE, WI 53209 (414) 462-3200

Emergency number: (800) 424-9300 - CHEMTREC

SECTION 2: Hazards identification

Classification of the substance or mixture: COMBUSTIBLE

Label elements: Aspiration Toxicity, Category 1

Flammable Liquids, Category 3



Other hazards: This material is classified as hazardous under OSHA regulations. Flammable liquid and vapor. Harmful if inhaled. Causes skin and eye irritation. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness.

Unknown acute toxicity (GHS-US): N/A

SECTION 3: Composition/information on ingredients

Substance: MIXTURE

Mixture

NAME	PRODUCT IDENTIFIER	% BY WT
Naphtha (petroleum), heavy alkylate	64742-47-8	75-80
DIMETHYL SILOXANE	63148-62-9	20-25

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general	
First-aid measures after inhalation	Remove to fresh air and get medical attention. If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.
First-aid measures after skin contact	Wash with soap and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.
First-aid measures after eye contact	Immediately flush eyes with water, remove any contact lens, continue flushing with water for at least 15 minutes. Get medical attention.



NEW TIRE SHINE SDS

First-aid measures after ingestion	Do not induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.
------------------------------------	---

Most important symptoms and effects, both acute and delayed: Delayed and immediate effects and also chronic effects from short- and long-term exposure: NONE.

Indication of any immediate medical attention and special treatment needed: NONE.

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media: Use carbon dioxide, dry chemical powder, or foam.

Unsuitable extinguishing media: Water

Advice for firefighters

Firefighting instructions - Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Protection during firefighting: N/A

SECTION 6: Accidental release measures

Personal precautions: Clean-up: Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.

Small spills: Take up the spilled liquid with sand, earth, or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Environmental precautions: Outside of normal use, avoid release to the environment.

Methods and materials for containment and cleaning up: Dike large spills.

Clean residue from spill site.

SECTION 7: Handling and storage

Precautions for safe handling: Avoid contact with skin, eyes and clothing.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Advice on protection against fire and explosion: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Requirements for storage areas and containers: Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

SECTION 8: Exposure controls/personal protection

Occupational Exposure Limits – For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.



NEW TIRE SHINE SDS

Personal protective equipment

Respiratory protection: Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately

Hand protection: Wear impermeable gloves. Gloves contaminated with product should be discarded.

Eye protection: Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Skin and body protection: Promptly remove clothing that becomes soiled with product. Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area.

SECTION 9: Physical and chemical properties

Form: liquid	Color: WHITE	Odor: Solvent odor
Melting/freezing point: N/A		Initial boiling point and boiling range: 250+ F
Approximate Evaporation rate: N/A		Flammability (solid, gas): both
U/L flammability or explosive limits Lower: 0.6%	Upper: 5.5%	Vapor pressure: no data
Vapor density: no data		Relative density: no data
Solubility: not soluble		Partition coefficient n-octanol/water: N/A
Auto-ignition temperature: N/A		Decomposition temperature: N/A
Viscosity – dynamic: N/A		Viscosity – kinematic: N/A
Oxidizing properties: N/A		Other information: None identified

SECTION 10: Stability and reactivity

Reactivity: NON REACTIVE

Chemical stability: STABLE

Possibility of hazardous reactions: NONE

Conditions to avoid (e.g., static discharge, shock, or vibration): N/A

Incompatible materials: STRONG OXIDIZING AGENTS

Hazardous decomposition products: Thermal decomposition may produce carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact): Skin, eyes, inhalation and ingestion.

Symptoms related to the physical, chemical and toxicological characteristics:

Skin contact – prolonged exposure can cause moderate irritation and dermatitis.

Eye contact – can cause severe irritation and redness.

Inhalation – Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

Ingestion - Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.



NEW TIRE SHINE SDS

Numerical measures of toxicity (such as acute toxicity estimates): N/A

SECTION 12: Ecological information

Eco-toxicity (aquatic and terrestrial, where available): The substance is harmful to aquatic organisms.

Persistence and degradability: N/A

Bio-accumulative potential: N/A

Mobility in soil: N/A

Other adverse effects (such as hazardous to the ozone layer): NONE

SECTION 13: Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

UN number: 1268

UN proper shipping name: Petroleum distillates, n.o.s.

Transport hazard class(es): 3

Packing group, if applicable: II

Environmental hazards (e.g., Marine pollutant (Yes/No)):

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): N/A

Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises: The shipper may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions

SECTION 15: Regulatory information

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

Yes No Acute (immediate) Health Hazard

Yes No Chronic (delayed) Health Hazard

Yes No Fire Hazard

Yes No Sudden Release of Pressure Hazard

Yes No Reactive Hazard



NEW TIRE SHINE SDS

SECTION 16: Other information

The information in this Safety Sheet was obtained from sources which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.