



SUPER COAT SDS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Name on Label: PROFESSIONALS CHOICE SUPER COAT

Other Identification: NONE

Use of the substance/mixture: GLOSS

Company name : MOORE OIL COMPANY
4033 WEST CUSTER AVE
MILWAUKEE, WI 53209 (414) 462-3200

Emergency number: (800) 424-9300 - CHEMTREC

SECTION 2: Hazards identification

Classification of the substance or mixture: GHS Classification Asp. Tox. 1, Eye Irrit. 2B, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 NE



Label elements: DANGER

SECTION 3: Composition/information on ingredients

MIXTURE

Chemical Name	CAS-No.	Wt. %
ALIPHATIC HYDROCARBON	64742-47-8	65-75
DIMETHYL SILOXANE, TRIMETHYLSILOXY-TERMINATED	63148-62-9	15-25
OTHER NON REPORTABLE INGREDIENTS		>1

SECTION 4: First aid measures

FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: Small amounts which accidentally enter mouth should be rinsed out until taste of it is gone. Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5: Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat,



SUPER COAT SDS

flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service and eliminate all sources of ignition. Avoid use of solid water streams. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6: Accidental release measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

SECTION 7: Handling and storage

HANDLING: Use only in a well-ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8: Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Aliphatic hydrocarbon	100 ppm	N.D.	500 ppm	N.D.

Personal Protection

RESPIRATORY PROTECTION: Wear a MSHA/NIOSH approved (or equivalent) full-face piece airline respirator in the positive pressure mode with emergency escape provisions.

SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.



SUPER COAT SDS

SECTION 9: Physical and chemical properties

Appearance: Clear, transparent liquid

Odor: Typical

Density, g/cm³: 0.782

Freeze Point, °F: N.D.

Solubility in Water: Insoluble

Boiling Range, °F: 318 - 386

Evaporation Rate: 0.21 (n-butyl acetate=1)

Vapor Density: 5 (air=1)

Physical State: Liquid

Odor Threshold: N.D.

pH: N.D.

Viscosity: N.D.

Explosive Limits, vol%: 0.8 - 6.0

Flash Point, °F: 104

Auto-ignition Temp., °F: N.D.

Vapor Pressure: N.D.

SECTION 10: Stability and reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Prevent contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11: Toxicological information

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. May cause central nervous system depression. Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes serious irritation to eyes. May cause tearing, redness and discomfort.

EFFECTS OF OVEREXPOSURE - INGESTION: May be fatal if swallowed and enters airway. Irritating to mouth, throat, and stomach. May cause nausea and vomiting. May cause central nervous system depression.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50, mg/kg	Dermal LD50, mg/kg	Vapor LC50, mg/L
64742-47-8	Aliphatic hydrocarbon	>5,000	>2,000	>20.0

SECTION 12: Ecological information

Eco-toxicity (aquatic and terrestrial, where available): none available

Persistence and degradability: none available

Bio-accumulative potential: none available

Mobility in soil: none available

Other adverse effects (such as hazardous to the ozone layer): none available



SUPER COAT SDS

SECTION 13: Disposal considerations

Always dispose of any waste in accordance with all local, state, and federal regulations. DISPOSAL

METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container

SECTION 14: Transport information

DOT Proper Shipping Name: Petroleum distillates, n.o.s. (naphtha solvent) - Combustible Liquid

Packing Group: III



DOT Hazard Class: No Information

Hazard SubClass: No Information

DOT UN/NA Number: UN1268

Resp. Guide Page: 128

SECTION 15: Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS



SUPER COAT SDS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer: No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS: This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

SECTION 16: Other information

The information in this Safety Sheet was obtained from sources which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.